



FEATURES:

- Dezincification resistant brass body
- Full bore
- Extended stem
- Lever operated

MATERIAL SPECIFICATION

Description	Material
Body	DZR Brass CW602N
Seat Retainer	DZR Brass CW602N
Ball	DZR Brass CW602N
Seat	PTFE
Stem	Brass CW614N
O-Rings (Packing)	EPDM & HNBR
Extension Stem	Brass CW614N
Extension Housing	Brass CW614N
Lever	Stainless Steel Type 304
Lever Cover	PVC

PRESSURE / TEMPERATURE RATING

25 Bar from -10°C to 100°C

HYDROSTATIC TEST PRESSURE

Shell: 37.5 bar

Seat: 27.5 bar

SPECIFICATION

Blow-out proof stem

extended stem

Quarter turn, lever operated

Full bore chrome plated ball

Two piece body

PTFE seats

Taper threaded to BS EN 10226-2 (ISO-7) formerly BS 21

DIMENSIONS & WEIGHT

DN	Inches	A (mm)	B (mm)	C (mm)	Weight (kg)
15	½	60	84	92	0.27
20	¾	67	87	92	0.35
25	1	76	95	105	0.51
32	1¼	93	108	134	0.87
40	1½	101	114	134	1.13
50	2	122	130	144	1.79

All dimensions are nominal (indicative). Actual dimensions may vary.

